




Model No.	Product Picture	Description
ECO-8990		<p>1.Size : $\phi 100*200*100$mm 2.Wattage :5W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK+GOLD /WHITE+GOLD 12.CCT :3000-3500K/6000-6500K</p>
ECO-8990		<p>1.Size : $\phi 100*200*100$mm 2.Wattage :5W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1107/Y		<p>1.Size : 140*100*115mm2.Wattage :3W*2 3.Kind of LED : COB Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :Adjustable 9.Lumens per Watt :110Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-1107/F		<p>1.Size : 100*100*100mm 2.Wattage :3W*2 3.Kind of LED : COB Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :Adjustable 9.Lumens per Watt :110Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8995		<p>1.Size : 125*40*60mm 2.Wattage :3W*2 3.Kind of LED : CREE USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :5° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-2055-1		<p>1.Size : 155*67*71mm 2.Wattage :3W*2 3.Kind of LED : CREE 3.Origin of LED :USA, 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :5° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-2055-2		<p>1.Size : 155*67*71mm 2.Wattage :3W*2 3.Kind of LED : CREE USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :5° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-2055-3		<p>1.Size : 155*67*71mm 2.Wattage :3W*2 3.Kind of LED : CREE 3.Origin of LED :USA, 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :5° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-6001		<p>1.Size : 130*160*H140mm 2.Wattage :10W*1 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :36° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-6003		<p>1.Size : 175*112*65mm 2.Wattage :3W*2 3.Kind of LED : CREE USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :5°+36° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-2404/T透镜款		<p>1.Size : 88*88*H208mm 2.Wattage :3W*2 3.Kind of LED : CREE USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :5°+36° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + glass+acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-5001C		<ol style="list-style-type: none"> 1.Size : 100*100*85mm 2.Wattage : 7W*1 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K
ECO-5001Z		<ol style="list-style-type: none"> 1.Size : 100*100*85mm 2.Wattage : 7W*1 3.Kind of LED : COB Bridgelux 3.Origin of LED :USA, 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K
ECO-5002		<ol style="list-style-type: none"> 1.Size : 170*100*85mm 2.Wattage : 7W*2 3.Kind of LED : COB Bridgelux 3.Origin of LED :USA, 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K
ECO-5005S		<ol style="list-style-type: none"> 1.Size : 183*38*67mm 2.Wattage :2W*3 3.Kind of LED : CREE 3.Origin of LED :USA, 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24°+180° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + glass+acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K

Model No.	Product Picture	Description
ECO-5005L		<ol style="list-style-type: none"> 1.Size : 280*60*93mm 2.Wattage :2W*5 3.Kind of LED : CREE USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24°+180° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + glass+acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K
ECO-7001		<ol style="list-style-type: none"> 1.Size : 200*105*55mm 2.Wattage :6W*1 3.Kind of LED : SMD Epistar Taiwan 4.Driver type :unidirectional voltage 5.Voltage :AC :110V / AC 220V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :Adjustable 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K
ECO-2101/2		<ol style="list-style-type: none"> 1.Size : 100*100*90mm 2.Wattage : 3W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K
ECO-2101/4		<ol style="list-style-type: none"> 1.Size : 100*100*90mm 2.Wattage : 3W*4 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K

Model No.	Product Picture	Description
ECO-8984		<p>1.Size : 120*120*H47mm 2.Wattage :1W*6 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :Adjustable 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8980/F		<p>1.Size : 130*130*50mm 2.Wattage :2W*4 3.Kind of LED : CREE USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8980/F		<p>1.Size : 130*130*50mm 2.Wattage :2W*4 3.Kind of LED : CREE USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24°+180° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-847		<p>1.Size : 75*75*55mm 2.Wattage :1W*4 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-8116		<ol style="list-style-type: none"> 1.Size : 190*45mm 2.Wattage :1W*3 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K
ECO-8608		<ol style="list-style-type: none"> 1.Size : 180*180*50mm 2.Wattage :1W*4 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K
ECO-8609		<ol style="list-style-type: none"> 1.Size : ϕ225*50mm 2.Wattage :1W*6 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K
ECO-8610		<ol style="list-style-type: none"> 1.Size : 80*80*35mm 2.Wattage :1W*4 3.Kind of LED :high power Epistar Taiwan 3.Origin of LED :Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :Adjustable 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K





Model No.	Product Picture	Description
ECO-8930/4		<p>1. Size : $\phi 95 \times 40 \text{mm}$ 2. Wattage : 1W*4 3. Kind of LED : high power Epistar 3. Origin of LED : Taiwan 4. Driver type : Wide voltage constant current drive 5. Voltage : AC : 85-265V 6. IP protection rate : IP54, 7. Life span (working hours) : 30000H 8. Beam angle : 24° 9. Lumens per Watt : 120Lm/1W 10. Material : Aluminum + acrylic</p>
ECO-8983		<p>1. Size : 155*72*H42mm 2. Wattage : 1W*3 3. Kind of LED : high power Epistar Taiwan 4. Driver type : Wide voltage constant current drive 5. Voltage : AC : 85-265V 6. IP protection rate : IP54, 7. Life span (working hours) : 30000H 8. Beam angle : Adjustable 9. Lumens per Watt : 120Lm/1W 10. Material : Aluminum + acrylic 11. Product Color : BLACK/GRAY 12. CCT : 3000-3500K/6000-6500K</p>
ECO-2017		<p>1. Size : 140*103*125mm 2. Wattage : 5W*1 3. Kind of LED : COB Bridgelux USA 4. Driver type : Wide voltage constant current drive 5. Voltage : AC : 85-265V 6. IP protection rate : IP54, 7. Life span (working hours) : 30000H 8. Beam angle : 24° 9. Lumens per Watt : 130Lm/1W 10. Material : Aluminum + glass+acrylic 11. Product Color : BLACK/GRAY 12. CCT : 3000-3500K/6000-6500K</p>
ECO-2018		<p>1. Size : 140*145*125mm 2. Wattage : 5W*2 3. Kind of LED : COB Bridgelux USA 4. Driver type : Wide voltage constant current drive 5. Voltage : AC : 85-265V 6. IP protection rate : IP54, 7. Life span (working hours) : 30000H 8. Beam angle : 24° 9. Lumens per Watt : 130Lm/1W 10. Material : Aluminum + glass+acrylic 11. Product Color : BLACK/GRAY 12. CCT : 3000-3500K/6000-6500K</p>


Model No.	Product Picture	Description
ECO-2070		<p>1.Size : 120*90*80mm 2.Wattage :3W*1 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-2071		<p>1.Size : 120*90*80mm 2.Wattage :3W*1 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-2072		<p>1.Size : 180*120*80mm 2.Wattage :3W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-2073		<p>1.Size : 180*120*80mm 2.Wattage :3W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>





Model No.	Product Picture	Description
ECO-8935		<p>1.Size : $\phi 65 \times H160$mm 2.Wattage :1W*2 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :Adjustable 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8935		<p>1.Size : $\phi 65 \times H160$mm 2.Wattage :1W*2 RGB 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic</p>
ECO-8607		<p>1.Size :250*90*35mm 2.Wattage :5W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :36° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8607		<p>1.Size :250*90*35mm 2.Wattage :5W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :36° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>





Model No.	Product Picture	Description
ECO-8601		<p>1.Size : 35*100*45mm 2.Wattage :1W*2 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8602		<p>1.Size : 85*100*45mm 2.Wattage :1W*4 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8603		<p>1.Size : 135*100*45mm 2.Wattage :1W*6 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :Adjustable 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8604		<p>1.Size : 185*100*45mm 2.Wattage :1W*8 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-8605		<p>1.Size :235*100*45mm 2.Wattage :1W*12 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8606		<p>1.Size : 285*100*45mm 2.Wattage :1W*12 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-3201		<p>1.Size : 80*80*50mm 2.Wattage :1W*2 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-3202/2		<p>1.Size : 110*80*50mm 2.Wattage :1W*4 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-3203/3		<p>1.Size :170*80*50mm 2.Wattage :1W*6 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-3204/4		<p>1.Size :220*80*50mm 2.Wattage :1W*8 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-3205/5		<p>1.Size :280*80*50mm 2.Wattage :1W*10 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-3206/6		<p>1.Size :320*80*50mm 2.Wattage :1W*12 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>





Model No.	Product Picture	Description
ECO-8870/S		<p>1.Size :155*63*67mm 2.Wattage :3W*2+3W 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass+acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8870/M		<p>1.Size :220*63*67mm 2.Wattage :3W*2+9W 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass+acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8870/L		<p>1.Size :365*64*63mm 2.Wattage :3W*2+15W 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass+acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-6002		<p>1.Size : 200*160*45mm 2.Wattage :15W*1 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-8871		<p>1.Size : 210*180*65mm 2.Wattage :9W*1 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8872		<p>1.Size : 240*130*80mm 2.Wattage :12W*1 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1120		<p>1.Size : ϕ170*100mm 2.Wattage :12W*1 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1121		<p>1.Size : ϕ170*100mm 2.Wattage :12W*1 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-3009		<p>1.Size : 230*110mm 2.Wattage :12W*1 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1911/1X		<p>1.Size : Φ65*H185mm 2.Wattage :3W*1 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1911/2X		<p>1.Size : Φ65*H280mm 2.Wattage :3W*2 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1910/1		<p>1.Size : Φ90*H165mm 2.Wattage :5W*1 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>



Model No.	Product Picture	Description
ECO-1910/2		<p>1.Size : $\Phi 90 \times H230$mm 2.Wattage :5W*2 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1913/1		<p>1.Size : $\Phi 90 \times H165$mm 2.Wattage :5W*1 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1913/2		<p>1.Size : $\Phi 90 \times H230$mm 2.Wattage :5W*2 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1915/1		<p>1.Size : $\Phi 90 \times H165$mm 2.Wattage :5W*1 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-1915/2		<p>1.Size : Ø90*H230mm 2.Wattage :5W*2 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8981/Y		<p>1.Size150*150*H50mm 2.Wattage :1W*4 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :5° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8981/F		<p>1.Size150*150*H50mm 2.Wattage :1W*4 3.Kind of LED :high power Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :5° 9.Lumens per Watt :120Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-3117		<p>1.Size : 165*165*42mm 2.Wattage :2W*4 3.Kind of LED : CREE USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :5° 9.Lumens per Watt :150Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-3002		<p>1.Size : 180*95mm 2.Wattage :1W*5 3.Kind of LED : Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :Adjustable 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-3003		<p>1.Size : 180*95mm 2.Wattage :1W*5 3.Kind of LED : Epistar Taiwan 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :Adjustable 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8023		<p>1.Size : 115*90*28mm 2.Wattage :3W*2 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8024		<p>1.Size : 175*90*28mm 2.Wattage :6W*2 3.Kind of LED : SMD SANAN China 4.Driver type :Wide voltage constant 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :120° 9.Lumens per Watt :100Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-8001		<p>1.Size :80*75*95mm 2.Wattage :3W*1 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8002		<p>1.Size :150*75*95mm 2.Wattage :3W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8003		<p>1.Size :185*75*95mm 2.Wattage :3W*1 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8004		<p>1.Size :150*70*92mm 2.Wattage :3W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-8005		<p>1.Size :ϕ80*76*63mm 2.Wattage :3W*1 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-8006		<p>1.Size :142*80*63mm 2.Wattage :3W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1160		<p>1.Size :Φ52*H325*W95mm 2.Wattage :3W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + acrylic 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-2502		<p>1.Size :68*171*H95mm 2.Wattage :3W*2 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>

Model No.	Product Picture	Description
ECO-1811		<p>1.Size :100*100*100mm 2.Wattage :3W*1 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>
ECO-1812		<p>1.Size :100*100*100mm 2.Wattage :3W*1 3.Kind of LED : COB Bridgelux USA 4.Driver type :Wide voltage constant current drive 5.Voltage :AC :85-265V 6.IP protection rate :IP54, 7.Life span (working hours) :30000H 8.Beam angle :24° 9.Lumens per Watt :130Lm/1W 10.Material : Aluminum + glass 11.Product Color : BLACK/GRAY 12.CCT :3000-3500K/6000-6500K</p>